Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7 (mm or inch): 18,2 mm or inch

and the second second

Order data

Order number	123035 18,2
GTIN	4045197840141
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.

The sector-leading technology of the drill point guarantees optimum self-centring behaviour. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 123036.

Form **HE:** order with **No. 123035 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 162.7 mm

Overall length L: 243 mm

Shank Ø D₅: 20 mm

Feed f in steel < 1100 N/mm²: 0.69 mm/rev.

Data sheet

Technical description

Number of cutting edges Z	3
Nominal Ø D _c	18.2 mm
Feed f in steel < 1100 N/mm ²	0.69 mm/rev.
Tolerance nominal Ø	h7
Flute length L _c	190 mm
Overall length L	243 mm
recommended maximum drilling depth L_2	162.7 mm
Shank Ø D _s	20 mm
Standard	Manufacturer's standard
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------