

# GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7 (mm or inch): 19,2 mm or inch



#### **Order data**

| Order number | 123035 19,2   |
|--------------|---------------|
| GTIN         | 4045197840189 |
| Item class   | 11E           |

#### **Description**

#### **Version:**

**3-flute drill**, specially developed for **use at very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- · Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.

The sector-leading technology of the drill point guarantees optimum self-centring behaviour. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

#### **Maximum drilling depth:**

flute length (see table) less  $1.5 \times \text{nominal } \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 123036.

Form **HE**: order with **No. 123035 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 161.2 mm

Overall length L: 243 mm Shank Ø D<sub>s</sub>: 20 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.69 mm/rev.

## **Technical description**

| Overall length L                                  | 243 mm                  |
|---|-------------------------|
| Shank Ø D <sub>s</sub>                            | 20 mm                   |
| Flute length L <sub>c</sub>                       | 190 mm                  |
| Tolerance nominal Ø                               | h7                      |
| Nominal Ø D <sub>c</sub>                          | 19.2 mm                 |
| Feed f in steel < 1100 N/mm <sup>2</sup>          | 0.69 mm/rev.            |
| Number of cutting edges Z                         | 3                       |
| Standard  | Manufacturer's standard |
| recommended maximum drilling depth L <sub>2</sub> | 161.2 mm                |
| Series  | GARANT Master Steel     |
| Coating   | TiAIN                   |
| Tool material                                     | Solid carbide           |
| Drill depth up to                                 | 8×D                     |
| Point angle                                       | 140 degrees             |
| Shank   | DIN 6535 HA to h6       |
| Through-coolant                                   | yes, to 25 bar          |
| Machining strategy                                | HPC                     |
| Semi-Standard                                     | yes                     |
| Colour ring                                       | green                   |
| Type of product                                   | Jobber drill            |
|   |                         |

### **Services**

| Shank grinding Type HE 129100 HE | Shank grinding Type HE | 129100 HE |
|----------------------------------|------------------------|-----------|
|----------------------------------|------------------------|-----------|