

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7 (mm or inch): 9,4 mm or inch



Order data

Order number	123035 9,4
GTIN	4045197839633
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.

The sector-leading technology of the drill point guarantees optimum self-centring behaviour. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 123036.

Form **HE**: order with **No. 123035 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 80.9 mm

Overall length L: 142 mm Shank Ø D_s: 10 mm

Feed f in steel < 1100 N/mm²: 0.44 mm/rev.

Technical description

Overall length L 142 mm recommended maximum drilling depth L_2 80.9 mm Shank \varnothing D_s 10 mm Feed f in steel < 1100 N/mm^2 0.44 mm/rev .Flute length L_c 95 mm Tolerance nominal \varnothing $h7$ Nominal \varnothing D_c 9.4 mm StandardManufacturer's standardNumber of cutting edges Z 3 SeriesGARANT Master SteelCoatingTiAIN
$\begin{array}{cccc} Shank \varnothing D_s & 10\text{mm} \\ Feed f \text{in steel} < 1100\text{N/mm}^2 & 0.44\text{mm/rev}. \\ Flute length L_c & 95\text{mm} \\ Tolerance nominal \varnothing & h7 \\ Nominal \varnothing D_c & 9.4\text{mm} \\ Standard & Manufacturer's standard \\ Number of cutting edges Z & 3 \\ Series & GARANT Master Steel \\ \end{array}$
Feed f in steel < 1100 N/mm² Flute length L _c 95 mm Tolerance nominal Ø Nominal Ø D _c Standard Number of cutting edges Z Series O.44 mm/rev. 95 mm h7 Namm Manufacturer's standard Manufacturer's standard GARANT Master Steel
Flute length L _c 95 mm Tolerance nominal Ø h7 Nominal Ø D _c 9.4 mm Standard Manufacturer's standard Number of cutting edges Z 3 Series GARANT Master Steel
Tolerance nominal Ø h7 Nominal Ø Dc 9.4 mm Standard Manufacturer's standard Number of cutting edges Z 3 Series GARANT Master Steel
Nominal Ø Dc9.4 mmStandardManufacturer's standardNumber of cutting edges Z3SeriesGARANT Master Steel
StandardManufacturer's standardNumber of cutting edges Z3SeriesGARANT Master Steel
Number of cutting edges Z Series 3 GARANT Master Steel
Series GARANT Master Steel
Coating
Couring
Tool material Solid carbide
Drill depth up to 8×D
Point angle 140 degrees
Shank DIN 6535 HA to h6
Through-coolant yes, to 25 bar
Machining strategy HPC
Semi-Standard yes
Colour ring green
Type of product Jobber drill

Services

Shank grinding Type HE	129100 HE
Shank grinding Type HE	129100 HE