Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC h7: 3 mm



Order data

Order number	123101 3
GTIN	4045197448828
Item class	11E

Description

Version:

Cutting chisel edge with high centring accuracy due to strong core and special point geometry.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

Convex cutting edges with honed edges and special flute profile for **short chips**, even on long chipping materials.

Advantage:

High process reliability and surface quality of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form **HB** and **HE** supplied at the same price as HA.

Form **HB:** order with **No. 123102**.

Form **HE:** order with **No. 123101 + 129100 HE**.

NEW GENERATION AVAILABLE!

Recommended successor products are No. 123025 and 123035.

Standard: Manufacturer's standard Tolerance nominal \emptyset : h7 Number of cutting edges Z: 2 Tolerance nominal \emptyset : h7 recommended maximum drilling depth L₂: 29.5 mm Overall length L: 72 mm Shank \emptyset D_s: 6 mm Feed f in steel < 1100 N/mm²: 0.1 mm/rev.

Technical description

Shank tolerance	h6
Number of cutting edges Z	2
Nominal Ø D _c	3 mm
Feed f in steel < 1100 N/mm ²	0.1 mm/rev.
Flute length L _c	34 mm
Tolerance nominal Ø	h7
Shank Ø D _s	6 mm
Overall length L	72 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	29.5 mm
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

129100 HE