

HOLEX
HOLEX Pro Steel solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 5,3 mm

Order data

| | |
|--------------|---------------|
| Order number | 123103 5,3 |
| GTIN | 4045197960252 |
| Item class | 12F |

Description
Version:
HOLEX Pro Steel:

Straight major cutting edges and a **special flute profile** ensure good chip evacuation. The robust cutting edge geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

Recommendation:
Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Version HB and HE supplied at the same price as HA.

Form **HB**: state **No. 123104**.

Form **HE**: state **No. 123109**.

Machining strategy: HPC

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 49.1 mm

Overall length L: 95 mm

Shank Ø D_s : 6 mm

Feed f in steel < 900 N/mm²: 0.13 mm/rev.

Technical description

| Standard | Manufacturer's standard |
|--|-------------------------|
| Tolerance nominal \varnothing | h7 |
| Nominal $\varnothing D_c$ | 5.3 mm |
| Overall length L | 95 mm |
| Number of cutting edges Z | 2 |
| recommended maximum drilling depth L_2 | 49.1 mm |
| Feed f in steel < 900 N/mm ² | 0.13 mm/rev. |
| Shank $\varnothing D_s$ | 6 mm |
| Flute length L_c | 57 mm |
| Series | HOLEX Pro Steel |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Drill depth up to | 8×D |
| Point angle | 135 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | Jobber drill |