

## Garant

**Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC h7: 11,5 mm**



### Order data

Order number	123110 11,5
GTIN	4045197357793
Item class	11E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### Advantage:

**High process reliability and surface quality of the hole.**

#### Recommendation:

#### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 123115**.

Form **HE**: order with **No. 123110 + 129100 HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 112.8 mm

Overall length L: 180 mm

Shank Ø  $D_s$ : 12 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.15 mm/rev.

### Technical description

Number of cutting edges Z	2
Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.15 mm/rev.
Flute length L <sub>c</sub>	130 mm
Nominal Ø D <sub>c</sub>	11.5 mm
Shank tolerance	h6
Tolerance nominal Ø	h7
Shank Ø D <sub>s</sub>	12 mm
Overall length L	180 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L <sub>2</sub>	112.8 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	10×D
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------