

## Garant

### Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC h7: 2,8 mm



#### Order data

Order number	123110 2,8
GTIN	4045197357304
Item class	11E

#### Description

##### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

##### Advantage:

**High process reliability and surface quality of the hole.**

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 123115**.

Form **HE**: order with **No. 123110 + 129100 HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 29.8 mm

Overall length L: 65 mm

Shank Ø  $D_s$ : 4 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.05 mm/rev.

#### Technical description

Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.05 mm/rev.
Flute length L <sub>c</sub>	34 mm
Nominal Ø D <sub>c</sub>	2.8 mm
Shank tolerance	h6
Number of cutting edges Z	2
Tolerance nominal Ø	h7
Shank Ø D <sub>s</sub>	4 mm
Overall length L	65 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L <sub>2</sub>	29.8 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	10×D
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill