

Garant

Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 14,2 mm



Order data

Order number	123115 14,2
GTIN	4045197402141
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

Straight major cutting edges with honed edges and special flute profile for **short chips**, even on long chipping materials.

Advantage:

High process reliability and surface quality of the hole.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 164.7 mm

Overall length L: 236 mm

Shank Ø D_s : 16 mm

Feed f in stainless steel < 900 N/mm²: 0.2 mm/rev.

Technical description

Number of cutting edges Z	2
Nominal Ø D_c	14.2 mm

Shank tolerance	h6
Feed f in stainless steel < 900 N/mm ²	0.2 mm/rev.
Flute length L _c	186 mm
Tolerance nominal Ø	h7
Shank Ø D _s	16 mm
Overall length L	236 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L ₂	164.7 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	10×D
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill