

**Garant**
**Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 3,4 mm**

**Order data**

Order number	123179 3,4
GTIN	4045197759627
Item class	11E

**Description**
**Version:**

**DLC coating**  $sp^2$  of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

**Recommendation:**
**Maximum drilling depth:**

clamping slot length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the  $12 \times D$  deep-hole drill, an initial centre drilling with No. 121068 – 121130 is necessary.

Standard: Manufacturer's standard

Tolerance nominal  $\varnothing$ : h7

Number of cutting edges Z: 2

Tolerance nominal  $\varnothing$ : h7

recommended maximum drilling depth  $L_2$ : 48.9 mm

Overall length L: 92 mm

Shank  $\varnothing D_s$ : 6 mm

Feed f in aluminium short-chipping: 0.35 mm/rev.

**Technical description**

Shank $\varnothing D_s$	6 mm
Standard	Manufacturer's standard
Nominal $\varnothing D_c$	3.4 mm
Number of cutting edges Z	2

Flute length $L_c$	54 mm
Feed $f$ in aluminium short-chipping	0.35 mm/rev.
Overall length $L$	92 mm
Shank tolerance	h6
Tolerance nominal $\varnothing$	h7
recommended maximum drilling depth $L_2$	48.9 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	12xD
Type	W
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill