

Garant

Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 5,9 mm



Order data

Order number	123179 5,9
GTIN	4045197759870
Item class	11E

Description

Version:

DLC coating sp^2 of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less $1.5 \times \text{nominal } \varnothing$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the $12 \times D$ deep-hole drill, an initial centre drilling with No. 121068 – 121130 is necessary.

Standard: Manufacturer's standard

Tolerance nominal \varnothing : h7

Number of cutting edges Z: 2

Tolerance nominal \varnothing : h7

recommended maximum drilling depth L_2 : 69.2 mm

Overall length L: 116 mm

Shank $\varnothing D_s$: 6 mm

Feed f in aluminium short-chipping: 0.45 mm/rev.

Technical description

Feed f in aluminium short-chipping	0.45 mm/rev.
Flute length L_c	78 mm
Number of cutting edges Z	2
Shank tolerance	h6

Overall length L	116 mm
Nominal $\varnothing D_c$	5.9 mm
Shank $\varnothing D_s$	6 mm
Tolerance nominal \varnothing	h7
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	69.2 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	12xD
Type	W
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill