

## Garant

**Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC m6 (mm or inch):  
11,5 mm or inch**



### Order data

Order number	123212 11,5
GTIN	4045197570444
Item class	11E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068– 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form **HB**: with **No. 123214**.

Order form **HE**: with **No. 123212 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Tolerance nominal Ø: m6

recommended maximum drilling depth  $L_2$ : 138.8 mm

Overall length L: 204 mm

Shank Ø  $D_s$ : 12 mm

Feed f in stainless steel > 900 N/mm<sup>2</sup>: 0.15 mm/rev.

### Technical description

Flute length $L_c$	156 mm
Shank tolerance	h6
Number of cutting edges Z	2
Feed f in stainless steel > 900 N/mm <sup>2</sup>	0.15 mm/rev.
Nominal $\varnothing D_c$	11.5 mm
Tolerance nominal $\varnothing$	m6
Shank $\varnothing D_s$	12 mm
Overall length L	204 mm
Standard	Manufacturer's standard
recommended maximum drilling depth $L_2$	138.8 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	12xD
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------