

## Garant

### GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 4,4 mm



#### Order data

|              |               |
|--------------|---------------|
| Order number | 123225 4,4    |
| GTIN         | 4045197844934 |
| Item class   | 11E           |

#### Description

##### Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- **Clear reduction in cutting forces due to special cutter geometry.**
- **Coating for best wear resistance even at high process temperatures.**
- **Polished flutes for good chip clearance.**

A **slim chisel point** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068 – 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form **HB**: with **No. 123226**.

Order form **HE**: with **No. 123225 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 57.4 mm

Overall length L: 102 mm

Shank Ø  $D_s$ : 6 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.1 mm/rev.

## Technical description

| Standard  | Manufacturer's standard |
|---|-------------------------|
| Number of cutting edges Z                         | 2                       |
| Overall length L                                  | 102 mm                  |
| Flute length L <sub>c</sub>                       | 64 mm                   |
| Feed f in steel < 1100 N/mm <sup>2</sup>          | 0.1 mm/rev.             |
| Shank Ø D <sub>s</sub>                            | 6 mm                    |
| Tolerance nominal Ø                               | h7                      |
| recommended maximum drilling depth L <sub>2</sub> | 57.4 mm                 |
| Nominal Ø D <sub>c</sub>                          | 4.4 mm                  |
| Series  | GARANT Master Steel     |
| Coating   | TiAlN                   |
| Tool material                                     | Solid carbide           |
| Drill depth up to                                 | 12×D                    |
| Point angle                                       | 135 degrees             |
| Shank   | DIN 6535 HA to h6       |
| Through-coolant                                   | yes, to 25 bar          |
| Machining strategy                                | HPC                     |
| Semi-Standard                                     | yes                     |
| Colour ring                                       | green                   |
| Type of product                                   | Jobber drill            |

## Services

|                        |           |
|------------------------|-----------|
| Shank grinding Type HE | 129100 HE |
|------------------------|-----------|