# Garant

# GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 7,1 mm

and a fill and the state of the same

# Order data

Order number	123225 7,1
GTIN	4045197845207
Item class	11E

### Description

#### Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- $\cdot\,$  Clear reduction in cutting forces due to special cutter geometry.
- $\cdot\,$  Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.
- A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

#### **Recommendation:**

#### Maximum drilling depth:

flute length (see table) less  $1.5 \times nominal \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068 – 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form **HB:** with **No. 123226**.

Order form **HE:** with **No. 123225 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 97.4 mm

Overall length L: 146 mm

Shank Ø D<sub>s</sub>: 8 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.15 mm/rev.

# **Technical description**

Feed f in steel < 1100 N/mm <sup>2</sup>	0.15 mm/rev.
Flute length L <sub>c</sub>	108 mm
Number of cutting edges Z	2
Nominal Ø D <sub>c</sub>	7.1 mm
Overall length L	146 mm
Standard	Manufacturer's standard
Tolerance nominal Ø	h7
Shank Ø D <sub>s</sub>	8 mm
recommended maximum drilling depth $L_2$	97.4 mm
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

# Services

Shank grinding Type HE

129100 HE