

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 8,7 mm



Order data

Order number	123225 8,7
GTIN	4045197845368
Item class	11E

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- · Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.

A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068 – 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form HB: with No. 123226.

Order form **HE:** with **No. 123225 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 2

Semi-Standard: yes Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 107 mm

Overall length L: 162 mm Shank Ø D_s: 10 mm

Feed f in steel < 1100 N/mm²: 0.18 mm/rev.

Technical description

recommended maximum drilling depth L_2	107 mm
Shank Ø D _s	10 mm
Nominal Ø D _c	8.7 mm
Flute length L _c	120 mm
Feed f in steel < 1100 N/mm ²	0.18 mm/rev.
Standard	Manufacturer's standard
Overall length L	162 mm
Number of cutting edges Z	2
Tolerance nominal Ø	h7
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE 129100 HE