

# GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 9 mm



## **Order data**

Order number	123225 9
GTIN	4045197845399
Item class	11E

# **Description**

#### **Version:**

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- · Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.

A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

#### **Recommendation:**

### Maximum drilling depth:

flute length (see table) less  $1.5 \times \text{nominal } \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068 – 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form HB: with No. 123226.

Order form **HE**: with **No. 123225 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 2

Semi-Standard: yes Tolerance nominal Ø: h7

recommended maximum drilling depth L<sub>2</sub>: 106.5 mm

Overall length L: 162 mm Shank Ø D<sub>s</sub>: 10 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.18 mm/rev.

# **Technical description**

2 5.5 mm mm
mm
h7
) mm
2 mm
rer's standard
0 mm
mm/rev.
yes
Master Steel
ïAlN
carbide
2×D
degrees
35 HA to h6
o 25 bar
HPC
reen
oer drill

# **Services**

Shank grinding Type HE 129100 HE