### Garant

# GARANT Master Steel SPEED solid carbide drill, Weldon shank DIN 6535 HB, TiAIN, Ø DC h7: 12,5 mm

1 met all and a for the

#### Order data

Order number	123226 12,5
GTIN	4045197848154
Item class	11E

#### Description

#### Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- $\cdot\,$  Clear reduction in cutting forces due to special cutter geometry.
- $\cdot\,$  Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.
- A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

#### **Recommendation:**

#### Maximum drilling depth:

Flute length (see table) less  $1.5 \times nominal \emptyset$ .

#### Note:

- Flute length  $L_c = L_2 + 1.5 \times D_c$ .
- For process reliability when using the 12×D deep-hole drill, an initial centre drilling with No.
- 121068 121130 or 3×D pilot drilling operation with No. 122736 is necessary.
- Standard: Manufacturer's standard
- Tolerance nominal Ø: h7
- Number of cutting edges Z: 2
- Tolerance nominal Ø: h7
- recommended maximum drilling depth L<sub>2</sub>: 163.3 mm
- Overall length L: 230 mm

Shank Ø D<sub>s</sub>: 14 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.23 mm/rev.

#### **Technical description**

## roup 🔥

## Data sheet

Tolerance nominal $\varnothing$	h7
Standard	Manufacturer's standard
Feed f in steel < 1100 N/mm <sup>2</sup>	0.23 mm/rev.
Flute length L <sub>c</sub>	182 mm
Overall length L	230 mm
Shank Ø D <sub>s</sub>	14 mm
Nominal Ø D <sub>c</sub>	12.5 mm
recommended maximum drilling depth $L_2$	163.3 mm
Number of cutting edges Z	2
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill