

GARANT Master Steel SPEED solid carbide drill, Weldon shank DIN 6535 HB, TiAIN, Ø DC h7: 8,4 mm



Order data

Order number	123226 8,4
GTIN	4045197847775
Item class	11E

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- · Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.

A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

Recommendation:

Maximum drilling depth:

Flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D deep-hole drill, an initial centre drilling with No.

121068 – 121130 or 3×D pilot drilling operation with No. 122736 is necessary.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 2 Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 107.4 mm

Overall length L: 162 mm Shank Ø D_s: 10 mm

Feed f in steel < 1100 N/mm²: 0.18 mm/rev.

Technical description

Flute length L_c	120 mm
Overall length L	162 mm
Feed f in steel < 1100 N/mm ²	0.18 mm/rev.
Standard	Manufacturer's standard
Number of cutting edges Z	2
Tolerance nominal Ø	h7
Nominal Ø D _C	8.4 mm
Shank Ø D _s	10 mm
recommended maximum drilling depth L ₂	107.4 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill