

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 10,9 mm



Order data

Order number	123235 10,9
GTIN	4045197840905
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.

The sector-leading technology of the drill point guarantees optimum self-centring behaviour. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D drill, an initial centre drilling with an NC spotting drill No. 121130 with **155° point angle** is necessary.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 139.7 mm

Overall length L: 204 mm Shank Ø D₆: 12 mm

Feed f in steel < 1100 N/mm²: 0.5 mm/rev.

Technical description



Tolerance nominal Ø	h7
Feed f in steel < 1100 N/mm ²	0.5 mm/rev.
recommended maximum drilling depth L ₂	139.7 mm
Flute length L _c	156 mm
Nominal Ø D _c	10.9 mm
Number of cutting edges Z	3
Standard	Manufacturer's standard
Shank Ø D _s	12 mm
Overall length L	204 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE 129100 HE