Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC h7: 11 mm

Order data

Order number	123301 11
GTIN	4045197452542
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.**

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

Convex cutting edges with honed edges and special flute profile for **short chips**, even on long chipping materials.

Advantage:

High process reliability and surface quality of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068 – 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Form **HB:** order with **No. 123302**.

Form **HE:** order with **No. 123301 + 129100HE**.

NEW GENERATION AVAILABLE!

Recommended successor products are No. 123225 and 123235.

Standard: Manufacturer's standard Tolerance nominal \emptyset : h7 Number of cutting edges Z: 2 Tolerance nominal \emptyset : h7 recommended maximum drilling depth L₂: 139.5 mm Overall length L: 204 mm Shank \emptyset D₃: 12 mm Feed f in steel < 1100 N/mm²: 0.2 mm/rev.

Technical description

Flute length L _c	156 mm
Number of cutting edges Z	2
Feed f in steel < 1100 N/mm ²	0.2 mm/rev.
Shank tolerance	h6
Nominal Ø D _c	11 mm
Tolerance nominal Ø	h7
Shank Ø D _s	12 mm
Overall length L	204 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	139.5 mm
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------