

# Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAIN, Ø DC h7: 4,8 mm



### **Order data**

Order number	123302 4,8
GTIN	4045197459145
Item class	11E

## **Description**

#### **Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** 

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Convex cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

## **Advantage:**

High process reliability and surface quality of the hole.

#### **Recommendation:**

## Maximum drilling depth:

clamping slot length (see table) less  $1.5 \times \text{nominal } \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the  $12\times D$  deep-hole drill, an initial centre drilling with No. 121068 - 121130 or  $3\times D$  pilot drilling operation with No. 122736 is necessary.

### **NEW GENERATION AVAILABLE!**

#### Recommended successor products are No. 123226 and 123236.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 2 Tolerance nominal Ø: h7

recommended maximum drilling depth L<sub>2</sub>: 70.8 mm

Overall length L: 116 mm

Shank Ø D<sub>s</sub>: 6 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.1 mm/rev.

# **Technical description**

Number of cutting edges Z	2
Shank tolerance	h6
Flute length L <sub>c</sub>	78 mm
Nominal Ø D <sub>c</sub>	4.8 mm
Feed f in steel < 1100 N/mm <sup>2</sup>	0.1 mm/rev.
Tolerance nominal Ø	h7
Shank Ø D <sub>s</sub>	6 mm
Overall length L	116 mm
Standard	Manufacturer's standard
recommended maximum drilling depth $L_2$	70.8 mm
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill