

**Garant**
**Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 7 mm**

**Order data**

Order number	123302 7
GTIN	4045197459237
Item class	11E

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Convex cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

**Advantage:**

**High process reliability and surface quality of the hole.**

**Recommendation:**
**Maximum drilling depth:**

clamping slot length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the 12×D deep-hole drill, an initial centre drilling with No. 121068 – 121130 or 3×D pilot drilling operation with No. 122736 is necessary.

**NEW GENERATION AVAILABLE!**

**Recommended successor products are No. 123226 and 123236.**

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 97.5 mm

Overall length L: 146 mm

Shank Ø  $D_s$ : 8 mm

Feed  $f$  in steel < 1100 N/mm<sup>2</sup>: 0.15 mm/rev.

## Technical description

Nominal $\varnothing D_c$	7 mm
Feed f in steel < 1100 N/mm <sup>2</sup>	0.15 mm/rev.
Number of cutting edges Z	2
Shank tolerance	h6
Flute length $L_c$	108 mm
Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	8 mm
Overall length L	146 mm
Standard	Manufacturer's standard
recommended maximum drilling depth $L_2$	97.5 mm
Semi-Standard	yes
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	12xD
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Colour ring	green
Type of product	Jobber drill