



Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiN, Ø DC h7: 10 mm



Order data

Order number	123308 10
GTIN	4045197451330
Item class	12E

Description

Version:

Strong core and special point geometry ensure the cutting chisel edges maintain **high self-centring accuracy**.

Straight cutting edges with slight edge hone and a special flute profile produce **short chips**.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D deep-hole drill, an initial centre drilling with No. 121068 – 121130 or 3×D pilot drilling operation with No. 122736 is necessary.

Pilot drill required: yes, pilot drill

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 105 mm

Overall length L: 162 mm

Shank Ø D_s : 10 mm

Feed f in steel < 1100 N/mm²: 0.2 mm/rev.

Technical description

Feed f in steel < 1100 N/mm ²	0.2 mm/rev.
Nominal Ø D_c	10 mm

Shank tolerance	h6
Number of cutting edges Z	2
Flute length L _c	120 mm
Tolerance nominal Ø	h7
Shank Ø D _s	10 mm
Overall length L	162 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L ₂	105 mm
Coating	TiN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Shank	DIN 6535 HE to h6
Through-coolant	yes, with 25 bar
Pilot drill required	yes, pilot drill
Colour ring	green
Type of product	Jobber drill