

Solid carbide HPC deep-hole drill plain shank DIN 6535 HA 16×D, DLC, Ø DC h7: 9 mm



Order data

Order number	123588 9
GTIN	4045197352491
Item class	11E

Description

Version:

Spiral fluted, with 6 guide chamfers and internal cooling channels. New generation of high performance deep hole drills in the HPC range. With 135° point angle and special h7 cutting edge tolerance for optimum generation of a deep hole. High roundness and alignment accuracy of the deep hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5 \times nominal \varnothing .

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the $16\times D$ deep hole drill, an initial centre drilling with No. 121068 - 121130 or $4\times D$ pilot drilling operation with pilot drill No. 122606 is necessary. For deep holes greater than $20\times D$, a $6\times D$ pilot hole with pilot drill No. 122606 is absolutely essential.

The generation of a pilot hole improves process reliability. See also pages 129/130.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 2 Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 146.5 mm

Overall length L: 205 mm Shank Ø D_s: 10 mm

Feed f in aluminium short-chipping: 0.33 mm/rev.

Technical description

Flute length L_c 160 mm

Number of cutting edges Z	2
Feed f in aluminium short-chipping	0.33 mm/rev.
Nominal Ø D _c	9 mm
Tolerance nominal Ø	h7
Shank Ø D _s	10 mm
Overall length L	205 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	146.5 mm
Coating	DLC
Tool material	Solid carbide
Drill depth up to	16×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 40 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Colour ring	yellow
Type of product	Jobber drill