

Garant

Solid carbide HPC deep-hole drill plain shank DIN 6535 HA 20xD, DLC, Ø DC h7: 3 mm



Order data

Order number	123590 3
GTIN	4045197353955
Item class	11E

Description

Version:

Spiral fluted, with **6 guide chamfers** and internal cooling channels. New generation of high performance deep hole drills in the HPC range. **With 135° point angle** and special **h7 cutting edge tolerance** for optimum generation of a deep hole. **High roundness and alignment accuracy of the deep hole.**

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 16xD deep hole drill, an initial centre drilling with No. 121068 – 121130 or 4xD pilot drilling operation with pilot drill No. 122606 is necessary. For deep holes greater than 20xD, a 6xD pilot hole with pilot drill No. 122606 is absolutely essential.

The generation of a pilot hole improves process reliability. See also pages 129/130.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 75.5 mm

Overall length L: 120 mm

Shank Ø D_s : 6 mm

Feed f in aluminium short-chipping: 0.14 mm/rev.

Technical description

Flute length L_c	80 mm
--------------------	-------

Number of cutting edges Z	2
Feed f in aluminium short-chipping	0.14 mm/rev.
Nominal $\varnothing D_c$	3 mm
Tolerance nominal \varnothing	h7
Shank $\varnothing D_s$	6 mm
Overall length L	120 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	75.5 mm
Coating	DLC
Tool material	Solid carbide
Drill depth up to	20×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 40 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Colour ring	yellow
Type of product	Jobber drill