

# Solid carbide HPC deep-hole drill plain shank DIN 6535 HA 30×D, TiAlN, $\varnothing$ DC h7: 9,8 mm

## **Order data**

Order number	123695 9,8
GTIN	4045197320568
Item class	11E

## **Description**

#### **Version:**

Spiral fluted, with **4 guide chamfers** and internal cooling channels. New generation of high performance deep hole drills in the HPC range.

With 135° point angle and special h7 cutting edge tolerance for optimum generation of a deep hole.

High roundness and alignment accuracy of the deep hole.

#### **Recommendation:**

### Maximum drilling depth:

Flute length (see table) less  $1.5 \times \text{nominal } \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the  $16\times D$  deep-hole drill, an initial centre drilling with No. 121068 - 121130 or  $4\times D$  pilot drilling operation with pilot drill No. 122736 is necessary. For deep holes greater than  $20\times D$ , a  $6\times D$  pilot hole with pilot drill No. 122736 is absolutely essential. **The generation of a pilot hole improves process reliability.** See also pages 129/130.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 2 Tolerance nominal Ø: h7

recommended maximum drilling depth L<sub>2</sub>: 315.3 mm

Overall length L: 380 mm Shank Ø D.: 10 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.16 mm/rev.

## **Technical description**

Flute length L<sub>c</sub> 330 mm

Feed f in steel < 900 N/mm <sup>2</sup>	0.16 mm/rev.
Nominal Ø D <sub>c</sub>	9.8 mm
Number of cutting edges Z	2
Tolerance nominal Ø	h7
Shank Ø D <sub>s</sub>	10 mm
Overall length L	380 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L <sub>2</sub>	315.3 mm
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	30×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 40 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Colour ring	green
Type of product	Jobber drill