

Garant

Solid carbide stepped drill for tapping holes 90°, TiAlN, for threads: M4



Order data

Order number	125100 M4
GTIN	4045197064950
Item class	11E

Description

Version:

Drill and counterbore each with its own chip flutes and guide chamfers. This special design permits frequent regrinding without losing the stepped drill profile. Countersink angle 90°.

Advantage:

Precisely aligned **tapping drill hole and countersink** produced **in a single operation**. For tapping drill holes.

No. of teeth Z: 2

Through-coolant: no

Ø D₁ 1st step with chamfer h7: 3.3 mm

Ø D₂ 2nd step with chamfer h7: 6 mm

Step height L₁ 1st step: 11.4 mm

Flute length L_c: 28 mm

Overall length L: 66 mm

Shank Ø D_s: 6 mm

Technical description

Feed f in steel < 1100 N/mm ²	0.08 mm/rev.
Ø D ₂ 2nd step with chamfer h7	6 mm
Ø D ₁ 1st step with chamfer h7	3.3 mm
Flute length L _c	28 mm
for threads	M4
Shank Ø D _s	6 mm
Overall length L	66 mm

Through-coolant	no
No. of teeth Z	2
Step height L ₁ 1st step	11.4 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	h7
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Countersink angle	90 degrees
Shank tolerance	h6
Colour ring	without
Type of product	Stepped drill