

**Garant**
**Hand tap, single Taper tap, uncoated, M: M30**

**Order data**

Order number	130160 M30
GTIN	4045197065704
Item class	11G

**Description**
**Version:**

Size M2.3 and M2.6 to old DIN profile.

Thread type: M

Tool material: HSS

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 3.5 mm

Overall length L: 125 mm

Shank  $\varnothing D_s$ : 22 mm

Shank square  $\square$ : 18 mm

Tapping hole  $\varnothing$ : 26.5 mm

**Technical description**

Tapping hole $\varnothing$	26.5 mm
Thread $\varnothing$	30 mm
Thread pitch	3.5 mm
Standard	DIN 352
Shank $\varnothing D_s$	22 mm
Overall length L	125 mm
Shank square $\square$	18 mm
Tolerance class	ISO 2 6H
Tool material	HSS

Thread depth	60 mm
Thread type	M
Thread size	M30
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	A
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Hand tap
Colour ring	without
Type of product	Tap