

Garant
Hand tap, single Taper tap, uncoated, M: M4

Order data

| | |
|--------------|---------------|
| Order number | 130410 M4 |
| GTIN | 4045197066336 |
| Item class | 11G |

Description
Version:

Tap, **consisting of the taper, second, and plug tap. Taper tap with long pilot.**

Thread type: M

Tool material: HSS E

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 0.7 mm

Overall length L: 45 mm

Shank $\varnothing D_s$: 4.5 mm

Shank square \square : 3.4 mm

Tapping hole \varnothing : 3.3 mm

Technical description

| | |
|----------------------------|----------|
| Thread pitch | 0.7 mm |
| Thread \varnothing | 4 mm |
| Tapping hole \varnothing | 3.3 mm |
| Standard | DIN 352 |
| Shank $\varnothing D_s$ | 4.5 mm |
| Overall length L | 45 mm |
| Shank square \square | 3.4 mm |
| Tolerance class | ISO 2 6H |
| Tool material | HSS E |

| | |
|----------------------------------|---|
| Thread depth | 8 mm |
| Thread type | M |
| Thread size | M4 |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | A |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for blind holes and through holes |
| Cutting direction | right-hand |
| Type of threading tool | Hand tap |
| Colour ring | without |
| Type of product | Tap |