

Hand tap set, uncoated, BSP: W5/8



Order data

| Order number | 130670 W5/8 |
|--------------|---------------|
| GTIN | 4045197067913 |
| Item class | 11G |

Description

Version:

Set of three, consisting of taper, second and plug tap.

Application:

For Whitworth threads to BSW standard BS84 in the tolerance field "medium".

Tool material: HSS
Threads per inch: 11
Thread Ø: 15.88 mm
Overall length L: 90 mm
Shank Ø D₅: 12 mm
Shank square □: 9 mm
Tapping hole Ø: 13.5 mm

Technical description

| Thread ∅ | 15.88 mm |
|------------------|----------|
| Threads per inch | 11 |
| Tapping hole ∅ | 13.5 mm |
| Thread pitch | 2.309 mm |
| Tool material | HSS |

| Shank Ø D _s | 12 mm |
|----------------------------------|---|
| Overall length L | 90 mm |
| Shank square □ | 9 mm |
| Thread depth | 31.76 mm |
| Thread size | W5/8 |
| Coating | uncoated |
| Thread type | BSW |
| Flank angle | 55 degrees |
| Standard | DIN 351 |
| Taper lead form | C |
| Taper lead form | D |
| Taper lead form | A |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for blind holes and through holes |
| Cutting direction | right-hand |
| Type of threading tool | Hand tap |
| Colour ring | without |
| Type of product | Тар |