

Garant
Hand tap set, uncoated, BSP: W7/32

Order data

Order number	130670 W7/32
GTIN	4045197067845
Item class	11G

Description
Version:

Set of three, **consisting of taper, second and plug tap.**

Application:

For Whitworth threads to BSW standard BS84 in the tolerance field "medium".

Tool material: HSS

Threads per inch: 24

Thread \varnothing : 5.56 mm

Overall length L: 50 mm

Shank \varnothing D_s: 6 mm

Shank square \square : 4.9 mm

Tapping hole \varnothing : 4.4 mm

Technical description

Thread \varnothing	5.56 mm
Threads per inch	24
Thread pitch	1.058 mm
Tapping hole \varnothing	4.4 mm
Tool material	HSS

Shank $\varnothing D_s$	6 mm
Overall length L	50 mm
Shank square \square	4.9 mm
Thread depth	11.12 mm
Thread size	W7/32
Coating	uncoated
Thread type	BSW
Flank angle	55 degrees
Standard	DIN 351
Taper lead form	C
Taper lead form	D
Taper lead form	A
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Hand tap
Colour ring	without
Type of product	Tap