

Hand tap set, uncoated, UNC: 8-32



Order data

| Order number | 130700 8-32 |
|--------------|---------------|
| GTIN | 4045197068019 |
| Item class | 11G |

Description

Version:

2-piece set comprising taper and plug tap.

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC
Tool material: HSS
Standard: DIN 351
Threads per inch: 32
Thread Ø: 4.16 mm
Overall length L: 45 mm
Shank Ø D₅: 4.5 mm
Shank square □: 3.4 mm
Tapping hole Ø: 3.5 mm

Technical description

| Thread Ø | 4.16 mm |
|------------------|----------|
| Threads per inch | 32 |
| Thread pitch | 0.794 mm |
| Tapping hole Ø | 3.5 mm |
| Standard | DIN 351 |
| Tool material | HSS |

Å Hoffmann Group

| Shank Ø D _s | 4.5 mm |
|----------------------------------|---|
| Overall length L | 45 mm |
| Shank square □ | 3.4 mm |
| Thread depth | 8.34 mm |
| Thread type | UNC |
| Thread size | 8-32 UNC |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Tolerance class | 2B |
| Taper lead form | D |
| Taper lead form | С |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for blind holes and through holes |
| Cutting direction | right-hand |
| Type of threading tool | Hand tap |
| Colour ring | without |
| Type of product | Тар |
| | |