

**Garant**
**Machine tap HSS-E, vaporised, M: M20**

**Order data**

Order number	131100 M20
GTIN	4045197068538
Item class	11H

**Description**
**Version:**
**Strong spiral point.**
**Guide section with oil grooves**, but without chip flutes. **Particularly strong, optimal self-guidance** with **no recutting** on reversal.

Sizes M2.3 and M2.6 to the old DIN profile.

**Callout:**

Oil groove

Guide thread

Lead-in

Spiral point

Thread type: M

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 2.5 mm

Overall length L: 140 mm

 Shank  $\varnothing D_s$ : 16 mm

 Shank square  $\square$ : 12 mm

 Tapping hole  $\varnothing$ : 17.5 mm

**Technical description**

Thread $\varnothing$	20 mm
Thread pitch	2.5 mm
Number of cutting edges Z	3

Number of clamping slots	3
Tapping hole Ø	17.5 mm
Standard	DIN 376
Shank Ø D <sub>s</sub>	16 mm
Overall length L	140 mm
Shank square □	12 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	60 mm
Thread type	M
Thread size	M20
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	yellow
Type of product	Tap