

**Garant****Machine tap HSS-E, vaporised, M: M3,5****Order data**

Order number	131100 M3,5
GTIN	4045197068453
Item class	11H

**Description****Version:****Strong spiral point.**

**Guide section with oil grooves**, but without chip flutes. **Particularly strong, optimal self-guidance with no recutting** on reversal.

Sizes M2.3 and M2.6 to the old DIN profile.

**Callout:**

Oil groove

Guide thread

Lead-in

Spiral point

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 0.6 mm

Overall length L: 56 mm

Shank  $\varnothing$  D<sub>s</sub>: 4 mm

Shank square □: 3 mm

Tapping hole  $\varnothing$ : 2.9 mm

**Technical description**

Thread pitch	0.6 mm
Number of cutting edges Z	2
Tapping hole $\varnothing$	2.9 mm
Thread $\varnothing$	3.5 mm

Number of clamping slots	2
Standard	DIN 371
Shank $\varnothing D_s$	4 mm
Overall length L	56 mm
Shank square $\square$	3 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	10.5 mm
Thread type	M
Thread size	M3.5
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	yellow
Type of product	Tap