

Garant
Machine tap Form B DIN 376, uncoated, M: M33

Order data

Order number	131200 M33
GTIN	4045197069207
Item class	11H

Description
Version:
With spiral point.
**All sizes: Shank to DIN 376(= shank Ø tapered), thus suitable for greater operating depths
 Sizes M2; M2.5; M3 without square. ISO 2 6H**
HSS

Thread type: M

Tool material: HSS

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 3.5 mm

Overall length L: 180 mm

 Shank Ø D_s: 25 mm

Shank square □: 20 mm

Tapping hole Ø: 29.5 mm

Technical description

Thread pitch	3.5 mm
Number of clamping slots	4
Thread Ø	33 mm
Number of cutting edges Z	4
Tapping hole Ø	29.5 mm
Standard	DIN 376
Shank Ø D _s	25 mm

Overall length L	180 mm
Shank square □	20 mm
Tolerance class	ISO 2 6H
Tool material	HSS
Thread depth	66 mm
Thread type	M
Thread size	M33
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap