

Garant
Machine tap Form B DIN 376, uncoated, M: M8

Order data

Order number	131200 M8
GTIN	4045197069092
Item class	11H

Description
Version:
With spiral point.
All sizes: Shank to DIN 376(= shank Ø tapered), thus suitable for greater operating depths
 Sizes M2; M2.5; M3 **without square. ISO 2 6H**
HSS-E

Thread type: M

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 1.25 mm

Overall length L: 90 mm

 Shank Ø D_s: 6 mm

Shank square □: 4.9 mm

Tapping hole Ø: 6.8 mm

Technical description

Number of cutting edges Z	3
Thread Ø	8 mm
Number of clamping slots	3
Tapping hole Ø	6.8 mm
Thread pitch	1.25 mm
Standard	DIN 376
Shank Ø D _s	6 mm

Overall length L	90 mm
Shank square □	4.9 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	16 mm
Thread type	M
Thread size	M8
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap