

Garant**Machine tap HSS-E-PM Form B, uncoated, M: M16****Order data**

Order number	131280 M16
GTIN	4045197069467
Item class	11H

Description**Version:****With spiral point.****Advantage:**

Greater wear resistance.

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 2 mm

Overall length L: 110 mm

Shank $\varnothing D_s$: 12 mmShank square \square : 9 mmTapping hole \varnothing : 14 mm**Technical description**

Thread \varnothing	16 mm
Tapping hole \varnothing	14 mm
Number of cutting edges Z	3
Number of clamping slots	3
Thread pitch	2 mm
Standard	DIN 376
Shank $\varnothing D_s$	12 mm
Overall length L	110 mm

Shank square <input type="checkbox"/>	9 mm
Tolerance class	ISO 2 6H
Tool material	HSS E PM
Thread depth	48 mm
Thread type	M
Thread size	M16
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap