

**Garant**
**Machine tap HSS-E-PM Form B, uncoated, M: M8**

**Order data**

Order number	131280 M8
GTIN	4045197069436
Item class	11H

**Description**
**Version:**
**With spiral point.**
**Advantage:**

Greater wear resistance.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 1.25 mm

Overall length L: 90 mm

 Shank  $\varnothing D_s$ : 8 mm

 Shank square  $\square$ : 6.2 mm

 Tapping hole  $\varnothing$ : 6.8 mm

**Technical description**

Number of cutting edges Z	3
Number of clamping slots	3
Tapping hole $\varnothing$	6.8 mm
Thread pitch	1.25 mm
Thread $\varnothing$	8 mm
Standard	DIN 371
Shank $\varnothing D_s$	8 mm
Overall length L	90 mm

Shank square <input type="checkbox"/>	6.2 mm
Tolerance class	ISO 2 6H
Tool material	HSS E PM
Thread depth	24 mm
Thread type	M
Thread size	M8
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap