



Spiral point tap stub, uncoated, M: M3



Order data

Order number	131600 M3
GTIN	4045197069825
Item class	12H

Description

Version:

With spiral point.

Application:

As hand or machine tap.

Thread type: M

Tool material: HSS E

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 0.5 mm

Overall length L: 40 mm

Shank $\varnothing D_s$: 3.5 mm

Shank square \square : 2.7 mm

Tapping hole \varnothing : 2.5 mm

Technical description

Thread pitch	0.5 mm
Number of cutting edges Z	3
Tapping hole \varnothing	2.5 mm
Number of clamping slots	3
Thread \varnothing	3 mm
Standard	DIN 352
Shank $\varnothing D_s$	3.5 mm

Overall length L	40 mm
Shank square □	2.7 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	6 mm
Thread type	M
Thread size	M3
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap