

Garant
Machine tap HSS-E, TiCN, M: M24

Order data

| | |
|--------------|---------------|
| Order number | 131930 M24 |
| GTIN | 4045197070852 |
| Item class | 11H |

Description
Version:
With spiral point.

For use with **emulsion** (fat content minimum 8%).

Recommendation:

For **TOOLOX** and **HARDOX materials** we recommend **deviating from the DIN data** (see table) by drilling the tapping hole \varnothing **0.05** to **0.3 mm** larger.

Thread type: M

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2X 6HX

Thread pitch: 3 mm

Overall length L: 160 mm

Shank \varnothing D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole \varnothing : 21 mm

Technical description

| | |
|----------------------------|---------|
| Number of clamping slots | 3 |
| Thread \varnothing | 24 mm |
| Thread pitch | 3 mm |
| Tapping hole \varnothing | 21 mm |
| Number of cutting edges Z | 3 |
| Standard | DIN 376 |

| | |
|----------------------------------|-----------------------------------|
| Shank $\varnothing D_s$ | 18 mm |
| Overall length L | 160 mm |
| Shank square \square | 14.5 mm |
| Tolerance class | ISO 2X 6HX |
| Tool material | HSS E |
| Thread depth | 72 mm |
| Thread type | M |
| Thread size | M24 |
| Coating | TiCN |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | B |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for through holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for dynamic machining |
| Colour ring | red |
| Type of product | Tap |