

Garant
Machine tap HSS-E-PM, TiN, M: M4

Order data

Order number	131935 M4
GTIN	4045197532312
Item class	11H

Description
Version:
With spiral point.

 For use also in **HARDOX materials (HARDOX ≤ 500)**.

 For use with **emulsion** (fat content minimum 8%).

Recommendation:

 For **TOOLOX** and **HARDOX materials** we recommend **deviating from the DIN data** (see table) by drilling the tapping hole \varnothing **0.05 to 0.3 mm** larger.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.7 mm

Overall length L: 63 mm

 Shank \varnothing D_s: 4.5 mm

Shank square □: 3.4 mm

 Tapping hole \varnothing : 3.3 mm

Technical description

Thread \varnothing	4 mm
Number of clamping slots	3
Number of cutting edges Z	3
Tapping hole \varnothing	3.3 mm
Thread pitch	0.7 mm
Standard	DIN 371

Shank $\varnothing D_s$	4.5 mm
Overall length L	63 mm
Shank square \square	3.4 mm
Tolerance class	ISO 2X 6HX
Tool material	HSS E PM
Thread depth	12 mm
Thread type	M
Thread size	M4
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap