

**Garant**
**Machine tap, uncoated, M: M4**

**Order data**

Order number	131950 M4
GTIN	4045197070890
Item class	11H

**Description**
**Version:**
**Sturdy version.**
**Recommendation:**

For **TOOLOX** and **HARDOX materials** we recommend **deviating from the DIN data** (see table) by drilling the tapping hole  $\varnothing$  **0.05 to 0.3 mm** larger.

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.7 mm

Overall length L: 63 mm

 Shank  $\varnothing$  D<sub>s</sub>: 4.5 mm

Shank square □: 3.4 mm

 Tapping hole  $\varnothing$ : 3.3 mm

**Technical description**

Tapping hole $\varnothing$	3.3 mm
Thread $\varnothing$	4 mm
Thread pitch	0.7 mm
Number of clamping slots	3
Number of cutting edges Z	3
Standard	DIN 371
Shank $\varnothing$ D <sub>s</sub>	4.5 mm

Overall length L	63 mm
Shank square □	3.4 mm
Tolerance class	ISO 2X 6HX
Tool material	HSS E
Thread depth	6 mm
Thread type	M
Thread size	M4
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap