

**Garant**
**Through hole machine tap with interrupted thread HSS-E-PM, uncoated, M: M2,5**

**Order data**

Order number	132400 M2,5
GTIN	4045197071392
Item class	11H

**Description**
**Version:**

**Sturdy design with 15° left-hand spiral.** With interrupted thread, this **reduces torque** and **improves distribution of the lubricant.**

Particularly suitable for **titanium alloys** and **pure titanium.**

**Advantage:**

**Ideally suited for use on resilient materials and thin-walled components.** Low frictional resistance, thus no material deformation is caused.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.45 mm

Overall length L: 50 mm

Shank  $\varnothing$  D<sub>s</sub>: 2.8 mm

Shank square □: 2.1 mm

Tapping hole  $\varnothing$ : 2.05 mm

**Technical description**

Tapping hole $\varnothing$	2.05 mm
Number of cutting edges Z	2
Number of clamping slots	2
Thread $\varnothing$	2.5 mm
Thread pitch	0.45 mm

Standard	DIN 371
Shank $\varnothing D_s$	2.8 mm
Overall length L	50 mm
Shank square $\square$	2.1 mm
Tolerance class	ISO 2X 6HX
Tool material	HSS E PM
Thread depth	5 mm
Thread type	M
Thread size	M2.5
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	D
Helix angle	15 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	pink
Type of product	Tap