

Garant
Through hole machine tap with interrupted thread HSS-E-PM, uncoated, M: M4

Order data

Order number	132400 M4
GTIN	4045197071415
Item class	11H

Description
Version:

Sturdy design with 15° left-hand spiral. With interrupted thread, this **reduces torque** and **improves distribution of the lubricant.**

Particularly suitable for **titanium alloys** and **pure titanium.**

Advantage:

Ideally suited for use on resilient materials and thin-walled components. Low frictional resistance, thus no material deformation is caused.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.7 mm

Overall length L: 63 mm

Shank Ø D_s: 4.5 mm

Shank square □: 3.4 mm

Tapping hole Ø: 3.3 mm

Technical description

Number of cutting edges Z	3
Number of clamping slots	3
Tapping hole Ø	3.3 mm
Thread Ø	4 mm
Thread pitch	0.7 mm

Standard	DIN 371
Shank $\varnothing D_s$	4.5 mm
Overall length L	63 mm
Shank square \square	3.4 mm
Tolerance class	ISO 2X 6HX
Tool material	HSS E PM
Thread depth	8 mm
Thread type	M
Thread size	M4
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	D
Helix angle	15 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	pink
Type of product	Tap