

Garant
Machine tap for cast iron, TiCN, M: M2

Order data

Order number	132550 M2
GTIN	4045197071866
Item class	11H

Description
Version:

With straight flutes and short chamfer lead (2 – 3 turns).

Advantage:

- **Improved wear properties due to hard coating.**
- **Higher cutting speeds due to reduction of thermal load on cutting edges.**
- **Dry machining possible on cast iron – cooling lubricant not necessary.**

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.4 mm

Overall length L: 45 mm

Shank \varnothing D_s: 2.8 mm

Shank square □: 2.1 mm

Tapping hole \varnothing : 1.6 mm

Technical description

Number of clamping slots	3
Tapping hole \varnothing	1.6 mm
Thread pitch	0.4 mm
Thread \varnothing	2 mm
Number of cutting edges Z	3
Standard	DIN 371

Shank $\varnothing D_s$	2.8 mm
Overall length L	45 mm
Shank square \square	2.1 mm
Tolerance class	ISO 2X 6HX
Tool material	HSS E
Thread depth	6 mm
Thread type	M
Thread size	M2
Coating	TiCN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3xD for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Maskinsnittapper til dynamisk bearbejdning
Colour ring	white
Type of product	Tap