

**Garant**
**Machine tap for synchronised spindles HSS-E-PM Form C, TiAlN, M: M8**

**Order data**

Order number	132555 M8
GTIN	4045197585288
Item class	11H

**Description**
**Version:**

**Sturdy design with shank to DIN 1835-B.** Special geometry for use on machines with **synchronised spindle drives**. The tap is controlled by the synchronising spindle of the machine. **Special TiAlN coating for optimum tool life.** For use with **emulsion** (fat content minimum 8 %).

Also outstandingly suitable for **bainite cast iron (ADI)**.

**Note:**

**For use on synchronised spindles**, the **GARANT** quick-change tapping chuck **No. 338100 – 338121 with minimum length adjustment (MLA)** ensures maximum process reliability.

Thread type: M

Tool material: HSS E PM

Standard: Manufacturer's standard

Tolerance class: ISO 2X 6HX

Thread pitch: 1.25 mm

Overall length L: 90 mm

Shank  $\varnothing D_s$ : 8 mm

Shank square  $\square$ : 6.2 mm

Tapping hole  $\varnothing$ : 6.8 mm

**Technical description**

Thread pitch	1.25 mm
Number of clamping slots	4
Thread $\varnothing$	8 mm
Number of cutting edges Z	4
Tapping hole $\varnothing$	6.8 mm

Standard	Manufacturer's standard
Shank $\varnothing D_s$	8 mm
Overall length L	90 mm
Shank square $\square$	6.2 mm
Tolerance class	ISO 2X 6HX
Tool material	HSS E PM
Thread depth	20 mm
Thread type	M
Thread size	M8
Coating	TiAlN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	DIN 1835 B with h6
Through-coolant	no
Application for type of drilling	up to 2.5xD for blind holes and through holes
Cutting direction	right-hand
Shank tolerance	h6
Type of threading tool	Machine tap for synchronous machining
Colour ring	white
Type of product	Tap