

Garant
Brass machine tap short, uncoated, M: M2

Order data

Order number	132600 M2
GTIN	4045197072092
Item class	11H

Description
Version:
With 6° flute angle and short chamfer lead (2 – 3 turns).
Application:

For use as machine tap or for cleaning existing threads by hand.

Thread type: M

Tool material: HSS E

Standard: DIN 352

Tolerance class: ISO 2 6H

Thread pitch: 0.4 mm

Overall length L: 36 mm

 Shank $\varnothing D_s$: 2.8 mm

 Shank square \square : 2.1 mm

 Tapping hole \varnothing : 1.6 mm

Technical description

Thread \varnothing	2 mm
Number of cutting edges Z	3
Thread pitch	0.4 mm
Tapping hole \varnothing	1.6 mm
Number of clamping slots	3
Standard	DIN 352
Shank $\varnothing D_s$	2.8 mm
Overall length L	36 mm

Shank square <input type="checkbox"/>	2.1 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	6 mm
Thread type	M
Thread size	M2
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	white
Type of product	Tap