

Garant
Machine tap HSS-E, vaporised, M: M1,7

Order data

Order number	132640 M1,7
GTIN	4045197072214
Item class	11H

Description
Version:
Spiral point with oil grooves.
Guide section with oil grooves, but without chip flutes.

Size M1.7, M2.3, and M2.6 with old DIN profile. **Tolerance class: ISO 2 6H**

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 0.35 mm

Overall length L: 40 mm

Shank $\varnothing D_s$: 2.5 mm

Shank square \square : 2.1 mm

Tapping hole \varnothing : 1.3 mm

Technical description

Thread \varnothing	1.7 mm
Number of clamping slots	2
Tapping hole \varnothing	1.3 mm
Thread pitch	0.35 mm
Number of cutting edges Z	2
Standard	DIN 371
Shank $\varnothing D_s$	2.5 mm
Overall length L	40 mm

Shank square <input type="checkbox"/>	2.1 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	5.1 mm
Thread type	M
Thread size	M1.7
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap