

# **GARANT Master Tap machine tap Form B 6HX, AITIX, M: M24**



### **Order data**

Order number	132721 M24
GTIN	4045197900470
Item class	111

## **Description**

#### **Version:**

**Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M

Tool material: HSS E PM Standard: DIN 376

Tolerance class: ISO 2X 6HX

Thread pitch: 3 mm Overall length L: 160 mm Shank Ø D<sub>s</sub>: 18 mm

Shank square □: 14.5 mm Tapping hole Ø: 21 mm

## **Technical description**

Standard	DIN 376
Tool material	HSS E PM
Number of clamping slots	4
Overall length L	160 mm
Thread depth	72 mm
Taper lead angle	7.93 degrees
Number of cutting edges Z	4

Shank Ø D <sub>s</sub>	18 mm
Tolerance class	ISO 2X 6HX
Tapping hole Ø	21 mm
Thread Ø	24 mm
Thread pitch	3 mm
Shank square □	14.5 mm
Thread type	M
Thread size	M24
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар