Garant

GARANT Master Tap machine tap Form B 6HX, AlTiX, M: M4



Order data

Order number	132721 M4
GTIN	4045197900388
Item class	111

Description

Version:

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- Special geometry for optimum swarf evacuation.

Thread type: M Tool material: HSS E PM Standard: DIN 371 Tolerance class: ISO 2X 6HX Thread pitch: 0.7 mm Overall length L: 63 mm Shank \emptyset D_s: 4.5 mm Shank square \Box : 3.4 mm Tapping hole \emptyset : 3.3 mm

Technical description

Shank square 🗆	3.4 mm
Overall length L	63 mm
Thread depth	12 mm
Thread pitch	0.7 mm
Taper lead angle	8.66 degrees
Tool material	HSS E PM
Standard	DIN 371

© Hoffmann GmbH Qualitätswerkzeuge

Number of clamping slots	3
Tapping hole \varnothing	3.3 mm
Tolerance class	ISO 2X 6HX
Number of cutting edges Z	3
Thread Ø	4 mm
Shank Ø Ds	4.5 mm
Thread type	М
Thread size	M4
Coating	AITiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар

Accessories

GARANT Master Tap through hole machine taps for metric	
	146435 M3-12
threads M3-12	11010011012