Garant

GARANT Master Tap machine tap Form B 6HX, AlTiX, M: M5



Order data

Order number	132721 M5
GTIN	4045197900395
Item class	111

Description

Version:

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- Special geometry for optimum swarf evacuation.

Thread type: M Tool material: HSS E PM Standard: DIN 371 Tolerance class: ISO 2X 6HX Thread pitch: 0.8 mm Overall length L: 70 mm Shank \emptyset D_s: 6 mm Shank square \Box : 4.9 mm Tapping hole \emptyset : 4.2 mm

Technical description

Number of clamping slots	3
Thread depth	15 mm
Tool material	HSS E PM
Shank square 🗆	4.9 mm
Thread Ø	5 mm
Standard	DIN 371
Thread pitch	0.8 mm

© Hoffmann GmbH Qualitätswerkzeuge

Shank Ø D _s	6 mm
Tolerance class	ISO 2X 6HX
Taper lead angle	8.66 degrees
Tapping hole Ø	4.2 mm
Number of cutting edges Z	3
Overall length L	70 mm
Thread type	М
Thread size	M5
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар

Accessories

GARANT Master Tap through hole machine taps for metric	
	146435 M3-12
threads M3-12	11015510512